



3 ph, 208 Volt - 60 Hz

Model	kVA LTP	kVA PRP	ENGINE								OPEN		SILENT			Fuel Tank Capacity lt
			Brand	Model	Prime Power kW	Displ. Lt	Asipration	Governor Type	Cylinder No	Cons. %75 lt/h	Dim. (WxLxH) mm	Weight kg	Dim. (WxLxH) mm	Weight kg	Sound @ 1 mt dB(A)	
IDJ40I6	38	35	FPT IVECO	S8000 AM1	31	2,9	NA	Mech	3	5,5	900x1600x1280	755	900x2250x1480	960	76	110
IDJ55I6	55	50	FPT IVECO	N45 AM1A	45	4,5	NA	Mech	4	8,3	900x1750x1310	820	900x2400x1500	1030	77	150
IDJ75I6	75	68	FPT IVECO	N45 SM1A	59	4,5	TC	Mech	4	10,1	900x1750x1310	895	900x2400x1500	1105	77	150
IDJ85I6	83	75	FPT IVECO	N45 SM2A	65	4,5	TC	Mech	4	11,5	900x1750x1310	920	900x2400x1500	1130	77	150
IDJ100I6	100	92	FPT IVECO	N45 SM3	79	4,5	TC	Mech	4	14,4	1000x1950x1410	1005	1000x2700x1610	1210	77	150
IDJ110I6	110	100	FPT IVECO	N45 TM1A	87	4,5	TC	Mech	4	15,2	1000x1950x1410	1250	1000x2700x1610	1355	78	150
IDJ120I6	121	110	FPT IVECO	N45 TM2A	97	4,5	TCA	Mech	4	16,8	1000x1950x1410	1355	1000x2700x1610	1460	78	150
IDJ160I6	160	145	FPT IVECO	N67 SM1	126	6,7	TC	Mech	6	21,0	1200x2400x1510	1480	1200x3400x1810	1780	78	200
IDJ300I6	300	270	FPT IVECO	N67 TE8W	230	6,7	TCA	Elec	6	35,4	1200x2600x1600	1560	1200x3520x1850	2020	79	220
IDJ350I6	350	315	FPT IVECO	C87 TE4	306	8,7	TCA	Elec	6	43,3	1300x3000x1680	2450	1300x3690x2100	3095	79	500
IDJ400I6	400	360	FPT IVECO	C87 TE4	306	8,7	TCA	Elec	6	49,0	1300x3000x1680	2690	1300x3690x2100	3335	79	500
IDJ425I6	425	385	FPT IVECO	C13 TE2A	327	12,9	TCA	Elec	6	50,2	1300x3200x2160	2790	1300x4500x2460	3435	79	600
IDJ475I6	475	430	FPT IVECO	C13 TE3A	360	12,9	TCA	Elec	6	56,2	1300x3200x2160	3040	1300x4500x2460	3685	80	600
IDJ560I6	560	510	FPT IVECO	C13 TE7	428	12,9	TCA	Elec	6	64,9	1300x3200x2160	3880	1300x4500x2460	4590	81	600
IDJ685I6	685	620	FPT IVECO	C16 TE1W	523	15,9	TCA	Elec	6	82,0	1500x3250x2160	4560	1650x4910x2450	5270	82	700

STANDARD EQUIPMENT

- Industrial engine, complete with cooling system, injection system with speed governor
- Industrial, brushless IP23 and H class alternator with electronic voltage control system
- Heavy Duty type , daily fuel tank integrated baseframe
- 12/24 Volt Battery
- Anti vibration mounts under the genset
- Industrial type exhaust silencer
- AMF Type Control Panel
- 3 poles MCCB
- Electrical Fuel Level Gauge
- Battery Cutoff switch
- Radiator Level sensor
- Lifting hooks

OPTIONAL EQUIPMENT

- Sound Proof Canopy completing with Residential type Exhaust Silencer or insulated exhaust pipes
- Critical type Exhaust Silencer
- 4 poles MCCB
- 3 / 4 poles ATS
- Coolant Heater
- Socket outlets
- Trailer
- Synchronization Panel
- Remote control / monitoring
- Fuel Prefilter
- Oversized Fuel Tank
- Lubrication and Fuel Heaters
- Auto fuel filling