



3 ph, 208 Volt - 60 Hz

Model	kVA LTP	kVA PRP	ENGINE								OPEN		SILENT			Fuel Tank Capacity lt
			Brand	Model	Prime Power kW	Displ. Lt	Asipration	Governor Type	Cylinder No	Cons. %75 lt/h	Dim. (WxLxH) mm	Weight kg	Dim. (WxLxH) mm	Weight kg	Sound @ 1 mt dB(A)	
IDJ12P6	12	10	PERKINS	403A-11G1	10	1,1	NA	Mech	3	2,3	800x1300x1100	415	800x1820x1150	585	76	60
IDJ17P6	17	16	PERKINS	403A-15G1	13	1,5	NA	Mech	3	2,8	900 X1480 X850	425	900X2100 X 900	595	76	60
IDJ27P6	27	24	PERKINS	404A-22G	22,3	2,2	NA	Mech	3	4,8	900 X1480 X850	505	900X2100 X 900	670	77	60
IDJ38P6	38	35	PERKINS	1103A-33G	32	3,3	NA	Mech	3	6,6	900X1600X1150	685	900x2250x1200	885	77	110
IDJ59P6	59	53	PERKINS	1103A-33TG1	49	3,3	TC	Mech	3	9,9	900X1600X1150	770	900x2250x1200	970	77	110
IDJ75P6	75	68	PERKINS	1103A-33TG2	61	3,3	TC	Mech	3	12,1	900X1750X1100	805	900X2400X1200	1005	77	110
IDJ84P6	84	76	PERKINS	1104A-44TG1	69	4,4	TC	Mech	4	13,5	900X1750X1100	920	900X2400X1200	1170	78	150
IDJ100P6	100	91	PERKINS	1104A-44TG2	82	4,4	TC	Mech	4	16,9	1000X1950X1200	950	1000X2700X1300	1200	78	150
IDJ127P6	127	114	PERKINS	1104C-44TAG2	102	4,4	TCA	Mech	4	20,2	1000X1950X1200	1070	1000X2700X1300	1320	78	150
IDJ169P6	169	152	PERKINS	1106A-70TG1	134	7,0	TC	Mech	6	26,5	1100X2300X1200	1470	1100 X3100X1350	1630	78	200
IDJ188P6	188	169	PERKINS	1106A-70TAG2	147	7,0	TCA	Mech	6	29,1	1100X2300X1200	1565	1100 X3100X1350	1725	78	200
IDJ219P6	219	197	PERKINS	1106A-70TAG3	173	7,0	TCA	Mech	6	35,3	1100X2400X1300	1650	1100X3300X1450	2010	78	300
IDJ275P6	275	250	PERKINS	1506A-E88TAG1	216	8,8	TCA	Elec	6	30,2	1100X2400X1300	1800	1100X3300X1450	2100	79	300
IDJ315P6	317	279	PERKINS	1506A-E88TAG3	266	8,8	TCA	Elec	6	39,3	1300X1800X1700	2330	1300X4000X1800	2870	79	400
IDJ358P6	358	325	PERKINS	1506A-E88TAG4	289	8,8	TCA	Elec	6	44,3	1300X1800X1700	2450	1300X4000X1800	2950	79	400
IDJ400P6	403	366	PERKINS	1506A-E88TAG5	321	8,8	TCA	Elec	6	50,0	1300X1800X1700	2500	1300X4000X1800	3000	79	400
IDJ440P6	440	400	PERKINS	2206C-E13TAG2	369	12,5	TCA	Elec	6	55,0	1300X3200X1700	2700	1300X4500X1800	3800	79	450
IDJ550P6	550	500	PERKINS	2506C-E15TAG1	454	15,0	TCA	Elec	6	68,0	1500X3200X1700	3100	1500X4500X1800	4400	80	600
IDJ560P6	560	510	PERKINS	2506C-E15TAG2	452	15,0	TCA	Elec	6	69,9	1500X3200X1700	3200	1500X4500X1800	4500	81	600
IDJ685P6	687	625	PERKINS	2806A-E18TAG1A	562	18,1	TCA	Elec	6	84,4	1650X3600X2120	3580	1650X4910X2450	4620	82	800
IDJ900P6	900	816	PERKINS	2806A-E18TTAG4	710	18,1	TCA	Elec	6	94,5	1650X3600X2120	3700	1650X4910X2450	4800	83	1000

### STANDARD EQUIPMENT

- Industrial engine, complete with cooling system, injection system with speed governor
- Industrial, brushless IP23 and H class alternator with electronic voltage control system
- Heavy Duty type , daily fuel tank integrated baseframe
- 12/24 Volt Battery
- Anti vibration mounts under the genset
- Industrial type exhaust silencer
- AMF Type Control Panel
- 3 poles MCCB
- Electrical Fuel Level Gauge
- Battery Cutoff switch
- Radiator Level sensor
- Lifting hooks

### OPTIONAL EQUIPMENT

- Sound Proof Canopy completing with Residential type Exhaust Silencer or insulated exhaust pipes
- Critical type Exhaust Silencer
- 4 poles MCCB
- 3 / 4 poles ATS
- Coolant Heater
- Socket outlets
- Trailer
- Synchronization Panel
- Remote control / monitoring
- Fuel Prefilter
- Oversized Fuel Tank
- Lubrication and Fuel Heaters
- Auto fuel filling