



3 ph, 208 Volt - 60 Hz

Model	kVA LTP	kVA PRP	ENGINE								OPEN		SILENT			Fuel Tank Capacity lt
			Brand	Model	Prime Power kW	Displ. Lt	Aspiration	Governor Type	Cylinder No	Cons. %75 lt/h	Dim. (WxLxH) mm	Weight kg	Dim. (WxLxH) mm	Weight kg	Sound @ 1 mt dB(A)	
IDJ17Y6	17	16	YANGDONG	YD385D	13	1,5	NA	Mech	3	3,67	900x1300x865	505	900x1850x1130	725	76	60
IDJ25Y6	24	22	YANGDONG	YND485D	20	2,2	NA	Mech	4	4,35	900x1480x915	550	900x2100x1185	770	77	60
IDJ30Y6	30	28	YANGDONG	YSD490D	25	2,5	NA	Mech	4	4,89	900x1480x915	560	900x2400x1500	780	77	60
IDJ40Y6	41	37	YANGDONG	Y495D	29	3,0	NA	Mech	4	6,22	900x1600x1165	600	900x2250x1550	850	77	100
IDJ45Y6	44	40	YANGDONG	Y4100D	36	3,7	NA	Mech	4	6,85	900x1600x1165	700	900x2250x1550	980	77	100
IDJ60Y6	61	56	YANGDONG	Y4110D	48	4,5	NA	Mech	4	10,18	900x1750x1350	820	900x2400x1550	1050	78	110
IDJ85Y	86	78	YANGDONG	Y4105ZLD	60	4,1	TC	Elec	4	12,76	1000x1950x1350	1200	1000x2700x1635	1480	78	150
IDJ95Y6	96	87	YANGDONG	YD4EZLD	70	4,1	TC	Elec	4	14,92	1000x1950x1350	1270	1000x2700x1635	1550	78	150
IDJ120Y6	119	108	YANGDONG	Y4110ZLD	90	4,3	TCA	Elec	4	18,69	1000x1950x1350	1320	1000x2700x1635	1570	79	150

STANDARD EQUIPMENT

- Industrial engine, complete with cooling system, injection system with speed governor
- Industrial, brushless IP23 and H class alternator with electronic voltage control system
- Heavy Duty type , daily fuel tank integrated baseframe
- 12/24 Volt Battery
- Anti vibration mounts under the genset
- Industrial type exhaust silencer
- AMF Type Control Panel
- 3 poles MCCB
- Electrical Fuel Level Gauge
- Battery Cutoff switch
- Radiator Level sensor
- Lifting hooks

OPTIONAL EQUIPMENT

- Sound Proof Canopy completing with Residential type Exhaust Silencer or insulated exhaust pipes
- Critical type Exhaust Silencer
- 4 poles MCCB
- 3 / 4 poles ATS
- Coolant Heater
- Socket outlets
- Trailer
- Synchronization Panel
- Remote control / monitoring
- Fuel Prefilter
- Oversized Fuel Tank
- Lubrication and Fuel Heaters
- Auto fuel filling