

### About Product

IDEA generator sets are designed to be used as backup or continuous power supply. They are subjected to detailed load and performance tests in our production facilities in order to provide ideal performance and safe usage.



### Power Output Values

Voltage	Standby Power (ESP)			Prime Power (PRP)		
	kVA	kW	Ampere	kVA	kW	Ampere
400/231	<b>2500 kVA</b>	2000 kW	3612,5	<b>2250 kVA</b>	1800 kW	3251

**Standby Power (ESP)** : This rating is for the supply of continuous electrical power at variable load , in the event of utility power failure. No overload is permitted.

**Prime Power (PRP)** : This rating is for the supply of continuous electrical power at variable load. There is no limitation on the annual hours in operation and 10% overload power can be supplied for 1 hour in 12.

### Weight And Dimensions

Type	Width x Length x Height (mm)	Weight (kg)	Fuel Tank (Lt)	Sound dB(A) @1mt
Open	2250x6050x2780 mm	12915 kg	3500	TBA
Soundproofed	2470x12200x3100 mm	18710 kg	3500	93



### Engine

Frequency		50 Hz
Output Rating	kW	2183
Manufacturer and Model		Perkins 4016-61TRG3
Fuel		Diesel
Injection		Direct
Aspiration		Turbocharged and Aircooled
Cylinders		16
Bore and Stroke	mm	160 x 190
Displacement	lt	61,123
Cooling		Water
Engine Oil Specification		SAE 15W40
Compression Ratio		13:1
Engine Oil Capacity	lt	213
Coolant Capacity (incl.radiator)	lt	260
Governor		Electronical
Air Filter		Dry element
<b>FUEL CONSUMPTION</b>		
100 % Load	lt/h	470
75 % Load	lt/h	344
50 % Load	lt/h	234
<b>EXHAUST SYSTEM</b>		
Maximum Temperature	°C	560
Exhaust Gas Flow	m <sup>3</sup> /min	525
Maximum Allowed Back Pressure	kPA	4
Exhaust Flange Size (Internal Dia.)	mm	254
<b>AIR SYSTEM</b>		
Intake Air Flow	m <sup>3</sup> /min	175
Total Cooling Air Flow	m <sup>3</sup> /min	2540
<b>STARTING SYSTEM</b>		
Starter Motor	kW	16,4
Battery Capacity	Ah	4x220
Auxiliary Voltage	V	24

### Alternator

Poles		4 pole
Winding Connections		Star
Insulation		Class H
Enclosure		IP23
Exciter System		Self regulating Brushless
Voltage Regulator		AVR
Steady State Voltage Regulation		± 1 %
Bearing		Single bearing sealed
Coupling		Flexible disc
Cooling		Direct drive centrifugal blower fan



### Control Panel IDP300

The new IDP300 genset controller is a cost effective modular genset controller ready for internet monitoring through plug-in modules.

Its main advantages are multifunctionality, support for multiple topologies, harmonic analysis and detailed power measurements.

Software features are complete with easy firmware upgrade through USB port. The Windows based PC software allows monitoring and programming through USB, RS-485, RS-232, Ethernet and GPRS.

The Rainbow Scada web service allows monitoring and control of an unlimited number of gensets from a single central location.



### Optional Equipments

Some Optional Equipment IDEA Provides with Generator Sets;

- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, instrument panel, alternator, coil heaters,
- Synchronization systems,
- Generator output fuse,
- Mains generator transfer switches,
- Seismic solutions,
- Remote monitoring
- Other requested solutions

### Reference Standards

IDEA Generator Sets are CE approved and comply with the following standards;

- Power according to ISO 3046 and ISO 8528
- EN 12100 , EN 13857 , EN 60204
- 2006/42/CE Machinery Safety
- 2006/95/EC Low Voltage
- 2004/108/CE EMC
- Ambient reference conditions 1000 mbar, 25 °C, 30 % relative humidity ISO8528

All the information in this leaflet is intended for general purposes only. IDEA reserves the right to change the specifications without notice.

